

TRPA Advisory Planning Commission  
October 9, 2019

Agenda Item V.A  
Technical Amendments to Chapters 2, 21, 30, 37, 50, 51, 53, and 84 of  
the TRPA Code of Ordinances

Errata Sheet

Exhibit 1 of Attachment A shall be revised as follows:

- (1) Item #7, an amendment to Subparagraph 50.5.2.E.2 shall be removed.
- (2) Item #12, an amendment to Subparagraph 84.3.3.E.1.c, shall be revised by adding the word “multiplied” to read as follows:

**CHAPTER 84: DEVELOPMENT STANDARDS LAKEWARD OF HIGH WATER IN THE  
SHOREZONE AND LAKEZONE**

---

**84.3. MOORING STRUCTURES**

**84.3.3. Mooring Buoys**

**E. Buoy Fields.**

**1. Eligibility.**

- c. The total number of buoys allowed within a buoy field shall not exceed the buoy field capacity. The maximum buoy field area, for the purposes of determining capacity, is the length of the littoral property’s lake frontage multiplied by a width of ~~within the area defined by the lake frontage, not including setbacks from parcel boundary projection lines, multiplied by~~ 300 feet (Figure 84.3.3-2). The capacity within the calculated buoy field area shall be limited by a 50-foot grid spacing pattern.